## Accessing the BIOS and changing the boot sequence

Created date	Updated date	Affects version	Fix version
13 Feb 2017	14 Feb 2023	All versions	N/A

In order to boot Blancco Driver Eraser (USB, CD, Network booting), the boot device containing the boot media needs to be set as the primary boot device.

To change the boot sequence, you must enter the "Setup" or "BISO/UEFI Setup" on your computer and change the booting sequence to use the USB drive /CD drive/Network adapter first. There are several ways to enter the setup depending on your computer manufacturer and model. During the booting stage a message will appear stating "Press DEL to enter Setup". As the message flashes only once on the screen, you must be quick to press the key before the boot sequence continues. Please note that the boot sequence may continue without any user intervention.

The [Delete] Key and [F2] are the two most common keys

We have collected some of the key combinations in order to get into the BIOS. On most systems you need to press these keys repeatedly during the POST (Power On Self-Test) as soon as the computer has been turned on. If the Windows Logo appears, you are too late, restart the computer and try again.

## **Computer Model BIOS Key examples:**

Manufacturer	BIOS Key		
Acer®	F1, F2, CTRL+ALT+ESC		
AST®	CTRL+ALT+ESC, CTRL+ALT+DEL		
Compaq® 8700	F10		
CompUSA®	DEL		
Cybermax®	ESC		
Dell®	F3, F1		
Dell Dimension	F2 or DEL		
Dell Inspiron	F2		
Dell Latitude	Fn+F1 (while booted)		
Dell Latitude	F2 (on boot)		
Dell Optiplex	F2 or DEL		
Dell Precision™	F2		
eMachine™	DEL		
Gateway®: 2000 1440	F1		
Gateway 2000 Solo™	F2		
HP	F1, F2		
IBM	F1		
IBM E-pro Laptop	F2		
IBM PS/2®	CTRL+ALT+INS after CTRL+ALT+DEL		
IBM Thinkpad® (newer)	Windows: Start   Programs   Thinkpad CFG		
Intel® Tangent	DEL		
Micron™:	F1, F2, or DEL		
Packard Bell®	F1, F2, DEL		
Sony® VAIO:	F2, F3		
Tiger	DEL		
Toshiba	F1 or ESC		